



Il incombe au client de s'assurer que la suggestion de pose est compatible avec la nature du sol.

CLASSE DE RESISTANCE - HORS DALOT (SELON NORME EN1433)		A15	B125	C250
QUALITE DU BETON DE POSE (NORME NF EN206-1)		C12/15	C12/15	C20/25
DIMENSIONS A RESPECTER POUR LA COULEE DU BETON DE POSE DU CANIVEAU	X (cm)	≥10	≥10	≥15
	Y (cm)	Jusqu'en en haut des cavités d'ancrage		
	Z (cm)	≥15	≥15	≥15

001	First revision		
index:	modification:		
technical reference:		general tolerance:	surface:
weight:		263.2 kg	
basic material:		document type:	
created by:		reviewed by:	
projection: ISO-E		scale:	
title:		1:1	
ACO sport		drawing-no.:	
Installation drawing ACO sport Channel N125 monoblock for impermeable synthetic coating		1392319	
Caniveau ACO sport N125 monobloc pour revêtement synthétique imperméable		index:	
The reproduction, distribution and utilization of this document as well as the communication of its contents to others without express authorization is prohibited. Offenders will be held liable for the payment of damages. All rights reserved in the event of the grant of a patent, utility model or design. Observe copyright by ISO 16016		001	
release date:		sheet:	
		1/1	